

HOLMEN

DECLARATION OF PERFORMANCE Machine strength graded structural timber

The undersigned, representing

Holmen Timber Braviken

herewith declares that the

Construction product

Machine strength graded structural timber which fulfills the requirements according to EN 14081-1:2005+A1:2011. For further or more detailed information on the delivered product, in addition to what is given below, see information on the packaging or in possible accompanying commercial document.

Intended use of the construction product

For load-bearing purposes in construction works designed according to Eurocode 5 (EN 1995) and for other uses where the strength and stiffness of the structure is essential.

Producer

Company: Holmen timber
Address: Bravikens sawmill
601 88 Norrköping
Sweden
Telephone: +46 650-280 00
E-mail: info@holmentimber.com
Web site: www.holmen.com

System of assessment and verification of constancy of performance of the construction product

System 2+.

Certification

The notified body SP Technical Research Institute of Sweden (identification number 0402) has performed an initial inspection of the manufacturing plant and of the factory production control and performs continuous surveillance, assessment and evaluation of our factory production control. SP has issued EC Certificate of Factory Production Control No. *0402-CPD-SC0405-11*.

Declared performance

Performance for machine strength graded structural timber in conformity with the harmonized European standard EN 14081-1:2005+A1:2011 Timber structures – Strength graded structural timber with rectangular cross section – Part 1: General

HOLMEN

requirements.

Essential characteristics

Declared performance

Species/species group	WPPA: spruce (<i>Picea abies</i>) and pine (<i>Pinus silvestris</i>)
Growth area	NNE Europe (Northern and North Eastern Europe)
Range of thickness (fire resistance)	26-110 mm Spruce , 35-70 mm Pine
Range of width (fire resistance)	58 -319 mm Spruce , 90-220 mm Pine
Surface finish	Sawn or planed
Dry or wet graded	Dry graded
Grading machine	ViScan
Strength, stiffness and density	<i>According to EN 338: C35, C30, C27, C24, C22, C20, C18 or C16; According to EN 14081-4 or relevant ITT-report: TR26</i>
Durability	4 (according to EN 350-2)
Reaction to fire	D-s2, d0 (according to EN 14081-1, Table C.1)
Release of dangerous substances	No dangerous substance to be declared

That the performance for our construction product machine strength graded structural timber is in accordance with the declared performance given above is certified:

Norrköping 2019-11-25

Holmen timber, Bravikens sawmill, 601 88 Norrköping


.....

Oreste Randolfi, Quality technician